


Hand Stretch Wrap film **Product Specification**



Description:

Hand-grade cast stretch wrap is quieter to apply, and has more cling than blown film. It also provides improved clarity over blown film for viewing bundle contents and requires less force to stretch the wrap during application, which reduces worker fatigue. It protects against dirt and moisture, keeps items together, and helps prevent tampering. These rolls are smaller than machine-grade wrap rolls, making them easier to transport around a facility.

<u>Technical Data:</u>	<u>US</u>	<u>Metric</u>	<u>Test Method</u>
Thickness	: 70 Gauge	17.78 μ m	ASTM D882
Width	: 12 in.	304.8mm	ASTM D882
Length	: 1500ft.	457.2m	ASTM D882
Tensile Strength	: MD 5511 psi TD 3045 psi	387kg/cm ² 203kg/cm ²	ASTM D882 ASTM D882
Elongation	: MD 415% TD 590%	---- ----	ASTM D882 ASTM D882

Application:

- ©To pack the pallets
- ©To pack the cartons
- ©To pack the equipment machine
- ©To pack some other bulk

Storage Conditions:

The Product has to be stocked in a dry environment, at a temperature about 32°F - 104°F . This product must be protected from dust, humidity, fire and direct sun exposure. It must be stored horizontally and kept in the original packaging.