


# **Machine Stretch Wrap film** **Product Specification**



## **Description:**

Machine-grade cast stretch wrap film is installed on a stretch wrap machine to wrap around uniform bundles. It protects the contents from tampering and damage, and is quieter to apply and has more cling than blown film. It also provides improved clarity over blown film for viewing bundle labeling and requires less force to stretch the wrap during application, reducing worker fatigue.

<b><u>Technical Data:</u></b>	<b><u>US</u></b>	<b><u>Metric</u></b>	<b><u>Test Method</u></b>
Thickness	: 120 Gauge	30.48 $\mu$ m	ASTM D882
Width	: 20 in.	508mm	ASTM D882
Length	: 4000ft.	1219.2m	ASTM D882
Tensile Strength	: MD 7251 psi TD 4496 psi	509kg/cm <sup>2</sup> 316kg/cm <sup>2</sup>	ASTM D882 ASTM D882
Elongation	: MD 600% TD 645%	----- -----	ASTM D882 ASTM D882

## **Application:**

- ©To pack the pallets
- ©To pack the cartons
- ©To pack the equipment machine
- ©To pack some other bulk

## **Storage Conditions:**

The Product has to be stocked in a dry environment, at a temperature about 32°F - 104°F . This product must be protected from dust, humidity, fire and direct sun exposure. It must be stored horizontally and kept in the original packaging.